

■マグネットワイヤ寸法表 (2種)

導体		最小皮膜 Conductor	最大仕上	銅		CCAW			
径 Dia. (mm)	許容差 Tolerance (mm)			Copper		Copper-clad Aluminum			
				厚さ Min.Film Thickness (mm)	外径 Max.O.D (mm)	最大導体抵抗 Max.Conductor Resistance (Ω/km 20°C)	概算質量 Approx.Wt. (kg/km)		
0.02	±0.002	0.003	0.030		69850	0.0028			
0.025	±0.002	0.003	0.037		42780	0.0049			
0.03	±0.002	0.003	0.044		28870	0.007			
0.04	±0.002	0.003	0.056		15670	0.012			
0.05	±0.003	0.004	0.069		10240	0.020			
0.06	±0.003	0.004	0.081		6966	0.027	9040 0.013		
0.07	±0.003	0.004	0.091		4990	0.036	6630 0.017		
0.08	±0.003	0.005	0.103		3778	0.048	5080 0.022		
0.09	±0.003	0.005	0.113		2959	0.060	4020 0.028		
0.10	±0.003	0.005	0.125		2381	0.074	3250 0.034		
0.11	±0.003	0.005	0.135		1957	0.089	2690 0.041		
0.12	±0.003	0.006	0.147		1636	0.11	2260 0.049		
0.13	±0.003	0.006	0.157		1389	0.12	1920 0.057		
0.14	±0.003	0.006	0.167		1193	0.14	1660 0.066		
0.15	±0.003	0.006	0.177		1037	0.16	1440 0.075		
0.16	±0.003	0.007	0.189		908.8	0.19	1270 0.086		
0.17	±0.003	0.007	0.199		803.2	0.21	1120 0.096		
0.18	±0.003	0.008	0.211		715.0	0.24	1000 0.10		
0.19	±0.003	0.008	0.221		640.6	0.26	900 0.12		
0.20	±0.003	0.008	0.231		577.2	0.29	812 0.13		
0.21	±0.003	0.008	0.241		522.8	0.32	737 0.15		
0.22	±0.004	0.008	0.252		480.1	0.35	672 0.16		
0.23	±0.004	0.009	0.264		438.6	0.38	613 0.17		
0.24	±0.004	0.009	0.274		402.2	0.42	564 0.19		
0.25	±0.004	0.009	0.284		370.2	0.45	520 0.20		
0.26	±0.004	0.009	0.294		341.8	0.49	482 0.22		
0.27	±0.004	0.009	0.304		316.6	0.52	446 0.24		
0.28	±0.004	0.009	0.314		294.1	0.57	415 0.25		
0.29	±0.004	0.009	0.324		273.9	0.60	387 0.27		
0.30	±0.005	0.010	0.337		254.0	0.65	361 0.29		
0.32	±0.005	0.010	0.357		222.8	0.73	318 0.33		
0.35	±0.005	0.010	0.387		185.7	0.88	265 0.39		
0.37	±0.005	0.010	0.407		165.9	0.98	238 0.44		
0.40	±0.005	0.011	0.439		141.7	1.14			
0.45	±0.006	0.011	0.490		112.1	1.44			
0.50	±0.006	0.012	0.542		89.95	1.78			
0.55	±0.006	0.012	0.592		74.18	2.15			
0.60	±0.008	0.012	0.644		62.64	2.56			
0.65	±0.008	0.012	0.694		53.26	3.00			
0.70	±0.008	0.013	0.746		45.84	3.47			
0.75	±0.008	0.014	0.798		39.87	3.99			
0.80	±0.010	0.015	0.852		35.17	4.54			
0.85	±0.010	0.015	0.904		31.11	5.12			
0.90	±0.010	0.016	0.956		27.71	5.74			

(JIS規格抜粋)